



ROPE SPECIFICATIONS

CAUTION: Working loads are tabulated for rope in good condition in non-critical applications and under normal service conditions. Working loads are not applicable where the rope is subjected to dynamic loading or other excessive use. Should the rope fail it may recoil with considerable force. Persons should be warned against standing in line with the rope.

DOUBLE BRAIDED POLYESTER				
Dia.	Size No.	Standard Tensile (LBS.)	Minimum Tensile (LBS.)	Aprox. Density (LBS./100')
1/4	3/4	2,150	1,935	2.0
5/16	1	3,300	2,975	3.1
3/8	1 1/8	4,750	4,275	4.5
7/16	1 1/4	6,375	5,725	6.1
1/2	1 1/2	8,250	7,425	8.0
9/16	1 3/4	10,250	9,225	10.1
5/8	2	12,500	11,250	12.5
3/4	2 1/4	17,800	16,000	17.9
7/8	2 3/4	24,000	21,600	24.4
1	3	31,200	28,100	31.9
1 1/8	3 1/2	39,500	35,550	40.4
1 1/4	3 3/4	48,600	43,750	49.8
1 5/16	4	53,600	48,250	55.0
1 1/2	4 1/2	69,000	62,100	71.8
1 5/8	5	80,000	72,000	84.0

- * **Premium Braid on Braid rope for Marine/ Electrical/ Utility Applications**
- * **100% High Tenacity Multifilament polyester in core and cover**
- * **High Strength with Low Stretch**
- * **Good Abrasion and Chemical Resistance**
- * **Readily Splicable using the buried, braid on raid procedure**
- * **Color: White with Gold Tracer**