

GLISS[®] F Metering Levels

The following table depicts approximate metering levels (gallons) of GLISS[®] F when pulling cable:

	1-1/4" Diameter	2" Diameter	3" Diameter	4" Diameter
100 feet	0.1	0.2	0.25	0.3
200 feet	0.2	0.3	0.50	0.6
300 feet	0.3	0.5	0.75	1.0
400 feet	0.4	0.6	1.00	1.3
500 feet	0.5	0.8	1.25	1.6
1,000 feet	1.0	1.6	2.50	3.2
2,000 feet	2.0	3.2	5.00	6.4
3,000 feet	3.0	4.8	7.50	9.6
4,000 feet	4.0	6.4	10.00	12.8
5,000 feet	5.0	8.0	12.50	16.0

Quantity can be reduced by 30-50% when an air compressor is used to pre-lubricate the conduit with GLISS[®] F.

When jetting cable in 1-1/4" inner-duct, the metering level is 3 to 8 ounces per 1,000 feet.

Recommended Use

	Inside Plant Cable Pulling	OSP Fiber Optic Cable Pulling	Large Conductor Cable Pulling	Fiber Optic Air Jetting	Cable Removal
GLISS [®]	Best	Good	Excellent	N/A	Best
GLISS[®] F	Excellent	Best	Excellent	Excellent	Excellent
GLISS [®] GEL	Excellent	N/A	Best	N/A	N/A